


TOPLINE SAFETY SPOT

Specification

Model	SAF-110	SAF-450	SAF-700
			
POWER	10W	20W	80W
DIMENSIONS	190*90*125mm	190*85*75mm	260*130*240mm
WEIGHT	1kg	1, 7kg	3. 1kg
COLOR TEMPERATURE	6500K	6500K	6500K
LUMINOUS FLUX, 1m	900-1200	1600-1700	9000-10000
BEAM ANGLE	20angle	20angle	20angle
INPUT VOLTAGE	110-240v	110-240v	110-240v
ADJUSTABLE ANGLE	90angle	All angles	All angles
ROTATING IMAGE	NO	YES	YES
INDOOR	YES	YES	YES
OUTDOOR	NO	YES	YES
INSTALATION	CEILING MOUNT	CEILING/WALL MOUNT	CEILING/WALL MOUNT
IP CLASS	IP33	IP65:Waterproof and dustproof	IP65:Waterproof and dustproof
Lifetime:	50000 hours	50000 hours	30000 hours
IMAGE CUSTOMIZATION	Any design. File type is needed: .ai; .cdr; or .jpg; the resolution should be not less than 1200*1200 pix	Any design. File type is needed: .ai; .cdr; or .jpg; the resolution should be not less than 1200*1200 pix	Any design. File type is needed: .ai; .cdr; or .jpg; the resolution should be not less than 1200*1200 pix
MAX. IMAGE DIAMETER AT A 3 METER DISTANCE	1,1 Meter	1,1 Meter	1,8 Meter
MINIMUM DISTANCE FOR THE PROJECTION	0,8 Meter	0,9 Meter	0,8 Meter

Max image sizes at distance of:	SAF-110	SAF-450	SAF-700
1m	0. 37m	0. 37m	0. 6m
2m	0. 743m	0. 743m	1. 2m
3m	1. 11m	1. 11m	1. 8m
4m	1. 48m	1. 48m	2. 4m
5m	1. 85m	1. 85m	3m
6m	2. 22m	2. 22m	3. 6m
7m	2. 59m	2. 59m	4. 2m
8m	2. 96m	2. 96m	4. 8m
9m	3. 33m	3. 33m	5. 4m
10m	3. 7m	3. 7m	6m